

SUNDRAY SI3200-08T-PWR-UN

Product Overview

Sundray SI3200-08T-PWR-UN Gigabit PoE switch is the component of enterprise WLAN solutions, with 8 gigabit PoE ports, can supply power for wireless AP by cable. Supporting 802.3af/802.3 at power supply standards, max output power is 30 W, mainly applied in middle-size and big-size wireless Wi-Fi networking.

Product Features

- Supporting IEEE802.3at(30W) standard, and being compatible with IEEE802.3af (15.4W) powered device (PD)
- The powered device complying with the IEEE 802.3at and IEEE 802.3af standard can be automatically detected;
- Advanced self-sensing arithmetic only supplies power for the terminal equipment with IEEE 802.3af/at standard; it is not necessary to worry about the Non-POE equipment or POE equipment with private standard being damaged;
- Power supply priority of the port is supported; the constant power supply of the key network nodes is ensured;
- The longest transmission distance of the power supplied by the cable is 100 meters, which can flexibly extent the network and not be restricted by the electric-power line, and easily hung up the terminal equipment such as the wireless AP and the web cam on the wall or the ceiling



SI3200-8T-PWR-UN

Specifications

SI3200-08T-PWR-UN

Specifications	
Item	SI3200-08T-PWR-UN (DUMP)
Fixed ports	Eight 10/100/1000M electrical ports (eight POE ports)
Standard of power supply	IEEE802.3af/at
Maximum output power of the single port	30W
Switch maximum POE output power	150W
POE power supply pin	1/2(+), 3/6(-); can be customized. 4/5(+),7/8(-)
Forwarding pattern	Storage forwarding with Full line rate
Forwarding rate	10M: 14880pps/port
	100M: 148809pps/port
	1000M: 1488095pps/port
Temperature for operating	-20~50 ℃
Storage temperature	-40~70 ℃
Working humidity	10%~90% non-condensing
Storage humidity	5%~95% non-condensing
Physical dimension	280 (L)*180(W)*44(H)mm
Input power	AC: 90 ~ 264V/50 ~ 60Hz/150W
Weight	<2Kg
LED indicator	Power, Link/Act, POE Status
Energy Saving and Environmental Protection	complying with the international standard of the “EEE” environmental protection and energy conservation
Protocol/standard	IEEE 802.3 af, Ethernet power supply POE standard;
	IEEE 802.3 at, Ethernet power supply POE+ standard;
	IEEE 802.3 u, Fast Ethernet standard;

	IEEE 802.3 ab, Gigabit Ethernet standard;
	IEEE 802.3x, full-duplex Ethernet data link layer flow control;
	IEEE 802.3 az, EEE energy-efficient Ethernet standard;
MAC address	Support 8K MAC address table
	Automatically update and dual-way learning are supported;
Port flow control	Half-duplex -based back pressure control is supported;
	Full duplex-based PAUSE frame is supported;
Jumbo frames	Support 9216Byte at the maximum
Physical medium	10/100Base-TX: type 3/4/5 twisted pair, transmission distance \leq 100M
	1000Base-T: type 5 twisted pair, transmission distance \leq 100M
	1000Base-SX: wave length--850nm optical fiber, transmission distance \leq 550M
	1000Base-LX: wave length--1310nm or 1550nm optical fiber, transmission distance \leq 80M
Cable sequence	Auto-MDIX function is supported; the Straight-through cable and crossover cable can be automatically identified;
Negotiation mode	The function of the automatic negotiation is supported by the port (self-negotiated transmission rate and the duplex mode);

Ordering information

SUNDRAY Gigabit POE switch		
Model	Specification	Remark
SI3200-08T-PWR-UN	PoE switch with eight Gigabit electrical ports, supporting 802.3af/at	Essential

SUNDRAY



Sundray Technologies Co, Ltd.

Address: Building A1, i Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China Post.

Post Code: 518055

www.sangfor.com

www.sundray.com

E-mail: liao haibo@sundray.com

Documentation version: 20150701-V2.6

Copyright © 2015 Shenzhen Sundray Technologies Company Ltd. All rights reserved.

DISCLAIMER: Sundray Technologies retains the rights of final explanation and modification of this document and this statement.